

# Sulphur dioxide

## Safety Data Sheet TYHJ-010

### SECTION 1: Product and company identification

#### 1.1. Product identifier

Product form	: Substance
Name	: Sulphur dioxide
CAS No	: 7446-09-5
Formula	: SO <sub>2</sub>
Other means of identification	: Sulfur Oxide, Sulfurous acid anhydride, Sulfur oxide, Sulfurous anhydride, Sulfurous oxide, Refrigerant gas R764

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Industrial use. Use as directed.
------------------------------	------------------------------------

#### 1.3. Details of the supplier of the safety data sheet

**TAIYU INDUSTRIAL GASES Limited**  
**16/F, Kowloon building, 555 Nathan**  
**Road, Mongkok Kowloon,**  
**Hong Kong**  
**TELEPHONE NUMBER: (852)22979277**

**Chengdu Taiyu Industrial Gases Co.,Ltd**  
**Chengluo Avenue, Longquan District,**  
**Chengdu City, China (Mainland)**  
**TELEPHONE NUMBER: (86) 28-88455212(commonly)**

#### 1.4. Emergency telephone number

Emergency number	: Onsite Emergency: <b>(86) 28-88455212</b>
------------------	---

CHEMTREC, 24hr/day 7days/week

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture


##### Classification (GHS-US)

Liquefied gas	H280
Acute Tox. 3 (Inhalation:gas)	H331
Skin Corr. 1B	H314
Eye Dam. 1	H318

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: DANGER

Hazard statements (GHS-US)

: H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED  
 H314 - CAUSES SEVERE SKIN BURNS AND EYE DAMAGE  
 H331 - TOXIC IF INHALED  
 CGA-HG22 - CORROSIVE TO THE RESPIRATORY TRACT

Precautionary statements (GHS-US)

: P202 - Do not handle until all safety precautions have been read and understood  
 P261 - Avoid breathing gas  
 P262 - Do not get in eyes, on skin, or on clothing.  
 P271+P403 - Use and store only outdoors or in a well-ventilated place.  
 P280+P284 - Wear protective gloves, protective clothing, eye protection, respiratory protection, and/or face protection.  
 P405 - Store locked up  
 P501 - Dispose of contents/container in accordance with container supplier/owner instructions  
 CGA-PG05 - Use a back flow preventive device in the piping.  
 CGA-PG20+CGA-PG10 - Use only with equipment of compatible materials of construction and



# Sulphur dioxide

## Safety Data Sheet TYHJ-010

rated for cylinder pressure.  
CGA-PG12 - Do not open valve until connected to equipment prepared for use.  
CGA-PG18 - When returning cylinder, install leak tight valve outlet cap or plug.  
CGA-PG06 - Close valve after each use and when empty.  
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

### 2.3. Other hazards

Other hazards not contributing to the classification : None.

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Name	Product identifier	%
Sulphur dioxide (Main constituent)	(CAS No) 7446-09-5	100

### 3.2. Mixture

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures after inhalation : Immediately remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.
- First-aid measures after skin contact : In case of contact, immediately flush affected areas with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician. Wash clothing before reuse. Discard contaminated shoes.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately.
- First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Exposure to concentrations above the TLV of 2 ppm may irritate the eyes, nose, throat, and sinuses, resulting in choking, coughing, and sometimes bronchoconstriction.

Concentrations of 50-100 ppm are considered dangerous.

Exposures of 400-500 ppm are immediately life-threatening.

Exposure to high concentrations may result in pulmonary edema and paralysis.

### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
- Reactivity : No reactivity hazard other than the effects described in sub-sections below.



# Sulphur dioxide

## Safety Data Sheet TYHJ-010

### 5.3. Advice for firefighters

- Firefighting instructions : **DANGER! Toxic, corrosive, high-pressure liquid and gas.**
- Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.
- Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : **DANGER: Toxic. Corrosive.** Wear a self-contained breathing apparatus and appropriate personal protective equipment (PPE). (gas tight, chemical-protective) Evacuate personnel to a safe area. Approach suspected leak area with caution. Remove all sources of ignition. Toxic, corrosive vapor can spread from spill. Ventilate area or move container to a well-ventilated area. Before entering the area, especially a confined area, check the atmosphere with an appropriate device.

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

### 6.3. Methods and material for containment and cleaning up

No additional information available

### 6.4. Reference to other sections

See also sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.
- Safe use of the product : Do not breathe gas/vapors. Use only with adequate ventilation or respiratory protection. Do not get liquid or vapor in eyes, on skin, or on clothing. Have safety showers and eyewash fountains immediately available.



# Sulphur dioxide

## Safety Data Sheet TYHJ-010

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

### 7.3. Specific end use(s)

None.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Sulphur dioxide (7446-09-5)		
ACGIH	ACGIH TLV-STEL (ppm)	0.25 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	13 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	5 ppm

### 8.2. Exposure controls

Appropriate engineering controls : Use only in a closed system. A corrosion-resistant, forced-draft fume hood is preferred. LOCAL EXHAUST: A corrosion-resistant system is acceptable.

In semiconductor process gas and other suitable applications, Praxair recommends the use of engineering controls such as gas cabinet enclosures, automatic gas panels (used to purge systems on cylinder changeout), excess-flow valves throughout the gas distribution system, double containment for the distribution system, and continuous gas monitors.

Eye protection : Provide readily accessible eye wash stations and safety showers. Wear safety glasses when handling cylinders; vapor-proof goggles and a face shield during cylinder changeout or whenever contact with product is possible. Select eye protection in accordance with OSHA 29 CFR 1910.133.

Skin and body protection : Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where needed. Wear appropriate chemical gloves (e.g. neoprene, nitrile, etc.) during cylinder changeout or wherever contact with product is possible. Select per OSHA 29 CFR 1910.132, 1910.136, and 1910.138.

Respiratory protection : When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure (e.g., an organic vapor cartridge). For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).

Thermal hazard protection : Wear cold insulating gloves when transfilling or breaking transfer connections.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Gas  
Appearance : Colorless, non-flammable gas.  
Molecular mass : 64 g/mol  
Color : Colorless.



# Sulphur dioxide

## Safety Data Sheet TYHJ-010

Odor	: Pungent. choking
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable.
Melting point	: -75.5 °C
Freezing point	: No data available
Boiling point	: -10 °C
Flash point	: Not applicable.
Critical temperature	: 157.6 °C
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 330 kPa
Critical pressure	: 7884 kPa
Relative vapor density at 20 °C	: No data available
Relative density	: 1.5
Specific gravity / density	: 1.39 g/cm <sup>3</sup> (at 20 °C)
Relative gas density	: 2.3
Solubility	: Water: Completely soluble.
Log Pow	: Not applicable for inorganic gases.
Log Kow	: Not applicable.
Viscosity, kinematic	: Not applicable.
Viscosity, dynamic	: Not applicable.
Explosive properties	: Not applicable.
Oxidizing properties	: None.
Explosion limits	: Non flammable.

### 9.2. Other information

Gas group	: Liquefied gas
Additional information	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

None.

### 10.4. Conditions to avoid

Avoid moisture in installation systems.

### 10.5. Incompatible materials

Moisture. Fluorine. Chlorine trifluoride. Chlorates. Sodium Carbide. Aluminum. (powdered). Zinc and its alloys. Manganese. Alkali metals. Metal nitrates. Rubidium carbide. Metal oxides. metal acetylides. Metal hydrides, flammable, n.o.s. Stannous oxide. Sodium. Acrolein (propenal).

### 10.6. Hazardous decomposition products

None known.



# Sulphur dioxide

## Safety Data Sheet TYHJ-010

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Inhalation:gas: TOXIC IF INHALED.

##### Sulphur dioxide ( f )7446-09-5

LC50 inhalation rat (ppm)	1260 ppm/4h
ATE US (gases)	1260.000 ppmV/4h

Skin corrosion/irritation : CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.  
Serious eye damage/irritation : CAUSES SERIOUS EYE DAMAGE.  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

##### Sulphur dioxide (7446-09-5)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified  
Specific target organ toxicity (single exposure) : Not classified  
Specific target organ toxicity (repeated exposure) : Not classified  
Aspiration hazard : Not classified  
Symptoms/injuries after inhalation : Exposure to concentrations above the TLV of 2 ppm may irritate the eyes, nose, throat, and sinuses, resulting in choking, coughing, and sometimes bronchoconstriction.

Concentrations of 50-100 ppm are considered dangerous.

Exposures of 400-500 ppm are immediately life-threatening.

Exposure to high concentrations may result in pulmonary edema and paralysis.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : No known ecological damage caused by this product.

#### 12.2. Persistence and degradability

##### Sulphur dioxide (7446-09-5)

Persistence and degradability	Not applicable for inorganic gases.
-------------------------------	-------------------------------------

#### 12.3. Bioaccumulative potential

##### Sulphur dioxide (7446-09-5)

BCF fish 1	(no bioaccumulation expected)
Log Pow	Not applicable for inorganic gases.
Log Kow	Not applicable.
Bioaccumulative potential	No data available.

#### 12.4. Mobility in soil

##### Sulphur dioxide (7446-09-5)

Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

# Sulphur dioxide

## Safety Data Sheet TYHJ-010

### 12.5. Other adverse effects

Other adverse effects	: May cause pH changes in aqueous ecological systems.
Effect on ozone layer	: None.
Effect on the global warming	: No known effects from this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations	: Do not attempt to dispose of residual or unused quantities. Return container to supplier.
--------------------------------	---

## SECTION 14: Transport information

In accordance with DOT

Transport document description	: UN1079 Sulfur dioxide, 2.3
UN-No.(DOT)	: UN1079
Proper Shipping Name (DOT)	: Sulfur dioxide
Department of Transportation (DOT) Hazard Classes	: 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115
Hazard labels (DOT)	: 2.3 - Poison gas 8 - Corrosive



DOT Special Provisions (49 CFR 172.102)	: 3 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone C (see 173.116(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter. B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials must not promote corrosion to steel when wet. T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter. TP19 - The calculated wall thickness must be increased by 3 mm at the time of construction. Wall thickness must be verified ultrasonically at intervals midway between periodic hydraulic tests (every 2.5 years). The portable tank must not be used if the wall thickness is less than that prescribed by the applicable T code in Column (7) of the Table for this material.
---	--

### Additional information

Emergency Response Guide (ERG) Number	: 125
Other information	: No supplementary information available.
Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

### Transport by sea

UN-No. (IMDG)	: 1079
Proper Shipping Name (IMDG)	: SULPHUR DIOXIDE
Class (IMDG)	: 2 - Gases
MFAG-No	: 125



# Sulphur dioxide

## Safety Data Sheet TYHJ-010

### Air transport

UN-No.(IATA)	: 1079
Proper Shipping Name (IATA)	: Sulphur dioxide
Class (IATA)	: 2
Civil Aeronautics Law	: Gases under pressure/Gases toxic under pressure

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

<b>Sulphur dioxide (7446-09-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Sudden release of pressure hazard

### 15.2. International regulations

<b>Sulphur dioxide (7446-09-5)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

### EU-Regulations

<b>Sulphur dioxide (7446-09-5)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

### 15.2.2. National regulations

<b>Sulphur dioxide (7446-09-5)</b>	
Listed on the AICS (Australian Inventory of Chemical Substances)	
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)	
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory	
Listed on the Korean ECL (Existing Chemicals List)	
Listed on NZIoC (New Zealand Inventory of Chemicals)	
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)	
Listed on the Canadian IDL (Ingredient Disclosure List)	

### 15.3. US State regulations

<b>Sulphur dioxide(7446-09-5)</b>	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List


## SECTION 16: Other information



# Sulphur dioxide

## Safety Data Sheet TYHJ-010

NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 0 - Materials that will not burn.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	: 0 Minimal Hazard
Physical	: 2 Moderate Hazard

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*